

NOTES:			
1.	DOOR PANEL - POLYURETHANE INSULATED		
	R32 @ 20°F 4" INSULATED		
	R48 @ 20°F 6" INSULATED		
	A.	COOLER DOOR 4" STANDARD	<input type="checkbox"/>
	B.	FREEZER DOOR 4" STANDARD	<input type="checkbox"/>
	C.	FREEZER DOOR 6" STANDARD	<input type="checkbox"/>
	HIGH HEAT INSULATION FOR UP TO 190°F		
	R23.7 @ 20°F 4" INSULATED		
	R39.7 @ 20°F 6" INSULATED		
	A.	COOLER DOOR 4" STANDARD	<input type="checkbox"/>
	B.	FREEZER DOOR 4" STANDARD	<input type="checkbox"/>
	C.	FREEZER DOOR 6" STANDARD	<input type="checkbox"/>
2.	DOOR , FRONT AND BACK, TO BE #26 GAUGE GALVANIZED STUCCO PATTERN EMBOSSED STEEL WITH BAKED-ON WITH ENAMEL FINISH, AS STANDARD. CASING FRAME TO BE PLYWOOD, METAL CLAD ON EXPOSED SURFACES TO MATCH DOOR.		<input type="checkbox"/>
3.	EXTERIOR GRADE PLYWOOD CASINGS AND JAMBS OF FRAME TO BE CLAD ON EXPOSED SURFACES WITH #24 GAUGE STAINLESS FINISH		
4.	HARDWARE - PER DOOR		
	SIX	"JB" ADJUSTOFLEX SELF-RAISING HINGES, GALVANIZED FINISH. (3 PER LEAF)	
	ONE	#220 TOP LATCH (REAR OF INACTIVE LEAF) WITH OFFSET STRIKE, AH4099-10	
5.	THREE - LARGE DOOR PULLS (ON BACK OF EACH LEAF AND ON FRONT OF INACTIVE LEAF). BH4038-1D		
6.	40" DIAMOND PLATE STANDARD WITH ALL DOORS		
7.	OPTIONS		YES NO
	A.	JAMBS, 1-1/2" PLYWOOD, CLAD TO MATCH DOOR	<input type="checkbox"/> <input type="checkbox"/>
	B.	INSIDE TRIM, 1-1/2" X 4-1/2" EXTRUDED ALUMINUM WITH BAKED-ON WHITE FINISH	<input type="checkbox"/> <input type="checkbox"/>
	C.	INSIDE TRIM, 1-1/2" x 4" PLYWOOD, CLAD TO MATCH DOOR	<input type="checkbox"/> <input type="checkbox"/>
	D.	DOOR SEALED TO MEET M.I.D. SPECIFICATIONS	<input type="checkbox"/> <input type="checkbox"/>
		GAUGE _____ HEIGHT _____	
	E.	KICKPLATE, DOOR FRONT	<input type="checkbox"/> <input type="checkbox"/>
		GAUGE _____ HEIGHT _____	
	F.	KICKPLATE, DOOR BACK	<input type="checkbox"/> <input type="checkbox"/>
		GAUGE _____ HEIGHT _____	
	G.	KICKPLATE, FRAME	<input type="checkbox"/> <input type="checkbox"/>
		GAUGE _____ HEIGHT _____	
	H.	VIEW WINDOW, 12" X 14" LEXAN	<input type="checkbox"/> <input type="checkbox"/>
		QUANTITY OF LAYERS _____	
	J.	OTHER	<input type="checkbox"/> <input type="checkbox"/>
8.	HEATERS PROVIDED AT HEAD, SIDES, AND HIGH SILL IN JAMB AREA OF FRAME. A THERMOSTAT IS PROVIDED FOR ENVIRO DOORS.		

